

DIN 8061 for PVC-u for PVCu (Metric) Fitting Dimensions						DIN 8063 for PVCu (Metric) Fitting Dimensions		
Diameter (mm)			Average Wall Thickness (mm)			Diameter (mm)		
Outside Diameter	Mean Outside Diameter		6 bar	10 bar	16 bar	Nominal Size	Mean Socket Internal Diameter At midpoint of Socket Depth	
	Minimum	Maximum					Minimum	Maximum
16	16	16.2	-	-	1.2	16	16.1	16.3
20	20	20.2	-	-	1.5	20	20.1	20.3
25	25	25.2	-	1.5	1.9	25	25.1	25.3
32	32	32.2	-	1.8	2.4	30	32.1	32.3
40	40	40.2	1.8	1.9	3.0	40	40.1	40.3
50	50	50.2	1.8	2.4	3.7	50	50.1	50.3
63	63	63.2	1.9	3.0	4.7	63	63.1	63.3
75	75	75.3	2.2	3.6	5.6	75	75.1	75.3
90	90	90.3	2.7	4.3	6.7	90	90.1	90.3
110	110	110.3	3.2	5.3	8.2	110	110.1	110.4
125	125	125.3	3.7	6.0	9.3	125	125.1	125.4
140	140	140.4	4.1	6.7	10.4	140	140.2	140.5
160	160	160.4	4.7	7.7	11.9	160	160.2	160.5
180	180	180.4	5.3	8.6	13.4	180	180.3	180.6
200	200	200.4	5.9	9.6	14.9	200	200.3	200.8
225	225	225.5	6.6	10.8	16.7	225	-	-
250	250	250.5	7.3	11.9	18.6	250	-	-
280	280	280.6	8.2	13.4	20.8	280	-	-
315	315	315.6	9.2	15.0	23.4	315	-	-