

SECURITHERM BIOCLIP thermostatic sink mixer

Ref. H9615

Single sequential mixer, stainless steel removable spout



DESCRIPTION

SECURITHERM BIOCLIP thermostatic sink mixer - Ref. H9615

Pillar-mounted thermostatic SECURITHERM sequential sink mixer with removable BIOCLIP spout.
Comes with 2 stainless steel spouts (ref. 20003) L. 135mm Ø 28mm for complete internal cleaning/descaling.
Anti-scalding safety: hot water shuts off immediately if cold water supply fails (and vice versa).
Securitouch thermal insulation prevents burns.
No non-return valves on the inlets.
Scale-resistant thermostatic sequential cartridge for single control temperature and flow-rate adjustment.
Adjustable temperature from cold water to 40°C with maximum temperature limiter set at 40°C.
Chemical and thermal shocks can be carried out.
Smooth interior body and spout, with low water volume (reduces niches where bacteria can develop).
Flow rate limited to 7 lpm at 3 bar.
No manual contact thanks to Hygiene control lever L. 146mm.
Chrome-plated brass body.
10-year warranty.

ADVANTAGES

-  Infection control
-  SECURITHERM: anti-scalding failsafe
-  Opens and closes via single control lever
-  Removable spout: reduces bacterial development

TECHNICAL FEATURES

SECURITHERM BIOCLIP thermostatic sink mixer - Ref. H9615

Connector	M1/2"
Technology	SECURITHERM BIOCLIP single control, Securitouch
Spout length	135mm
Flow rate	7 lpm
Temperature limiter	40°C
Finish	Chrome-plated brass
Warranty	

