

Stainless Steel Ball Valve - Butt Weld

LV 6302

Butt Weld, Full Bore, CF8M Stainless Steel Body, Ball & Stem, PTFE Seats & Seals, Anti-blowout Stem, Locking Device



Pressure / Temperature Specifications	
Pressure	PN63
Temperature	-10°C to 180°C

Material Specifications					
1	Body	CF8M Stainless Steel	10	Handle	304 Stainless Steel
2	Ball	CF8M Stainless Steel	11	Bolt	304 Stainless Steel
3	Thrust Washer	PTFE	12	Hex Nut	304 Stainless Steel
4	Stem Packing	PTFE	13	Spring Washer	304 Stainless Steel
5	Stem	316 Stainless Steel	14	Seat	PTFE
6	Gland Nut	304 Stainless Steel	15	Joint Gasket	PTFE
7	Stem Washer	304 Stainless Steel	16	Cover	Plastic
8	Stem Nut	304 Stainless Steel	17	Locking Device	304 Stainless Steel
9	Cap	CF8M Stainless Steel			

Dimensions						
Size	W	H	L	d	D	Kg
1/4"	105	48	61	12.5	15.2	0.4
3/8"	105	48	61	12.5	17.2	0.4
1/2"	105	50	63	15	22.5	0.6
3/4"	126	56	78	20	27.5	0.8
1"	144	67	86	25	34	1.1
1 1/4"	144	72	97	32	43	1.9
1 1/2"	189	93	113	38	50	2.6
2"	189	101	134	50	62	3.9

